

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LASER

Product code: 606

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

1.3. Details of the supplier of the safety data sheet

Company name: Clover Chemicals Ltd

Clover House

Macclesfield Road

Whaley Bridge, High Peak

Derbyshire

SK23 7DQ

UK

Tel: +44 (0) 1663 733114

Fax: +44 (0) 1663 733115

Email: technical@cloverchemicals.com

1.4. Emergency telephone number

Emergency tel: NHS 111

NHS Direct Wales 08454647

ROI 01 809 2166

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Aquatic Chronic 3: H412; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304; -: EUH066

Most important adverse effects: Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.
Harmful to aquatic life with long lasting effects. May be fatal if swallowed and enters airways.
Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

SAFETY DATA SHEET

LASER

Page: 2

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

H304: May be fatal if swallowed and enters airways.

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P282: Wear eye protection.

P280: Wear protective gloves.

P302+352: IF ON SKIN: Wash with plenty of water/.

P332+313: If skin irritation occurs: Get medical attention.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical attention.

P273: Avoid release to the environment.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

PETROLEUM DISTILLATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-149-8	64742-47-8	-	Asp. Tox. 1: H304	30-50%

HYDROCARBONS,C9-C11,N-ALKANES,ISOALKANES CYCLICS <2% AROMATICS

265-150-3	64742-48-9	-	Flam. Liq. 3: H226; STOT SE 3: H336; Asp. Tox. 1: H304; -: EUH066	10-30%
-----------	------------	---	--	--------

[cont...]

SAFETY DATA SHEET

LASER

Page: 3

2-BUTOXYETHANOL - REACH registered number(s): 01-2119475108-36-XXXX

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
-----------	----------	---	---	-------

ALKYL (C15 - C17) IMIDAZOLINE

263-171-2	61791-39-7	-	Aquatic Chronic 1: H410; Skin Corr. 1C: H314; Acute Tox. 4: H302; Aquatic Acute 1: H400	<1%
-----------	------------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Wash out mouth with water. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

[cont...]

SAFETY DATA SHEET

LASER

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition.

Suitable packaging: Stainless steel. Polyethylene.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PETROLEUM DISTILLATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000 mg/m ³	-	-	-

2-BUTOXYETHANOL

UK	25 ppm	50 ppm	-	-
----	--------	--------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Hand protection: Gloves (solvent-resistant).

Eye protection: Safety glasses with side-shields.

Skin protection: Oil-resistant protective clothing.

Section 9: Physical and chemical properties

[cont...]

SAFETY DATA SHEET

LASER

Page: 5

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale brown

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: No data available.

Melting point/range°C: -20

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: 61

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.8 - 0.9

pH: non aqueous

VOC g/l: 880

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Sources of ignition.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

LASER

Page: 6

HYDROCARBONS,C9-C11,N-ALKANES,ISOALKANES CYCLICS <2% AROMATICS

ORL	RAT	LD50	>5000	mg/kg
-----	-----	------	-------	-------

2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water. Floats on water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Incineration on land.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

LASER

Page: 7

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H410: Very toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.